



Technical features:

- Galvanized steel case, height 64 mm
- Galvanized steel faceplate
- Adjustable latchbolt, 11 to 17 mm
- 3-throw deadbolt, 11 mm
- Square spindle, 8 mm
- Cylinder fixing via lock internal screw

Supplied as standard:

- Threaded fixing pins for bushings and extended bolts, item 1.06449.05.0
- Pair of steel roses item 1.06075.00.0
- Pair of threaded bushings (M8) item 1.06290.05.0
- Instruction sheet
- Fixing screws


On request:

- Adjustable metal striker plates
- Modular roller assembly item 1.06168.00.0
- Nylon rose item 1.06141.56.0 ensuring interchangeability with series 57300
- Cylinder protective rose item 06460.05.50/51/60/61.0

Cylinder to be ordered separately




Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight	Pieces	ITEM			
								Type	Dim.	Hand	Fin.



- Stainless steel faceplate 25x3 mm
- Reversible latch and dead-bolt
- On request
 - "MODULAR" roller assembly item 1.06168.00.0
 - Floor striker item 1.06086.00/02.0
 - Zinc-plated steel striking plate item 1.06232.01.0 or item 1.06232.00.0
 - Cylinder protective rose item 106460.05/50/51/60/61
 - Rose for locks series 57300 item 1.06141.56.0 or item 1.06473.00.0
 - Extended bolts item 1.06441.15.0
 - Extended bolts with screws item 1.07088.03/05.0

3 67 25 90 0,930 12 1 56358 90 0



- MODULAR roller assembly for locks series 56357 and 56358

0,040 12 1 06168 00 0