



**Technical features:**

- Case height 82 mm
- Zinc plated case
- Zinc plated faceplate
- Brass latch, roller and bolt
- Electrical versions are interchangeable with item 44115/6 and item 44145/6
- Current absorption 1,3 A
- Voltage 12 V ac CE

**Supplied as standard:**

- Cylinder fixing screws
- Instruction sheet (if this is provided for)

**On request:**

- Specific striking plates (see Vademecum)
- Mechanical control button item 1.06110.10.0

**Hand:**

0 = Non-handed




1 = R.H. inwards

2 = L.H. inwards

**Cylinder to be ordered separately**



Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces	ITEM					
								Type	Dim.	Hand	Fin. Pers. Spec.		
	• Dead-locking latch	48	16	58	0,530	12	1	14010	60	1			
		48	16	58	0,530	12	1	14010	60	2			
		48	20	58	0,550	12	1	14011	60	1			
		48	20	58	0,565	12	1	14011	60	2			
	• Dead-locking latch • Hold-open latch	48	16	58	0,556	12	1	14012	60	1			
		48	16	58	0,556	12	1	14012	60	2			
	• Dead-locking latch • Low impact piston spring • Hold-open latch	48	16	58	0,557	12	1	14017	60	1			
		48	16	58	0,557	12	1	14017	60	2			
		• Dead-bolt only	2	16	58	0,485	12	1	44110	60	0		
			2	20	58	0,485	12	1	44111	60	0		
		• Dead-bolt only • Interchangeable with 14010 series	2	16	58	0,475	12	1	44115	60	0		
			2	20	58	0,485	12	1	44116	60	0		
	• Dead-bolt and non-handed latch	2	48	16	58	0,553	12	1	44120	60	0		
		2	48	20	58	0,570	12	1	44121	60	0		

Type	Description	Throws	Centre Distance	Faceplate Backset	Unit weight Kg	Pieces	ITEM				
							Type	Dim.	Hand	Fin.	Pers. Spec.
 <ul style="list-style-type: none"> <li>• Dead-bolt and adjustable roller</li> </ul>		2	16	58	0,517	12	1	44130	60	0	
		2	20	58	0,530	12	1	44131	60	0	
 <ul style="list-style-type: none"> <li>• Non-handed latch-bolt</li> <li>• Latch-bolt with incorporated dead-bolt</li> </ul>		1	48	16	58	0,500	12	1	44140	60	0
		1	48	20	58	0,510	12	1	44141	60	0
 <ul style="list-style-type: none"> <li>• Non-handed latch-bolt</li> <li>• Latch-bolt with incorporated dead-bolt</li> <li>• Interchangeable with series 14010</li> </ul>		1	48	16	58	0,500	12	1	44145	60	0
		1	48	20	58	0,515	12	1	44146	60	0