



Technical features:

- Zinc plated steel case
- Stainless steel faceplate
- Nickel-plated latch, roller, bolt and hook bolt
- Latch or reversible latch/bolt (if this is provided for)
- Current absorption 3,1A
- Voltage 12 V ac CE

Supplied as standard:

- Set of faceplate spacers item 1.06141.65.0
- Lock and cylinder fixing screws
- Instruction sheet

On request:

- Special striker plates (see Vademecum)
- Cylinder protective rose item 1.06460.00.0
- Cylinder with pin key series 02400
- Mechanical control button item 1.06110.10.0
- Threaded bushing item 1.06290.05 for extended bolts

Certification:


- This lock series is certified according to the European standard EN 12209:03 - Security class 3 (500 Kg side thrust and 400 Kg front thrust resistance)
- Suitable for doors certified to EN1627:2011 up to WK/RC 2 resistance class

Hand:
0 = Non-handed

Cylinder to be ordered separately




Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM			
								Type	Dim.	Hand	Fin. Spec.




- 10.5 to 16.5 mm. adjustable latch and piston
- Set of nylon roses item 1.06012.01.0

85	22	25	0,746	1	1	16205 25 0
85	22	30	0,770	1	1	16205 30 0
85	22	35	0,815	1	1	16205 35 0



- Dead-bolt and latch
- 10.5 to 16.5 mm. adjustable latch and piston
- Set of nylon roses item 1.06012.01.0


1	85	22	25	0,780	1	1	16215 25 0
1	85	22	30	0,825	1	1	16215 30 0
1	85	22	35	0,865	1	1	16215 35 0



- Cross-key cylinder with 3 keys
- Dead-bolt and latch
- 10.5 to 16.5 mm. adjustable latch and piston
- Set of nylon roses item 1.06002.00.0


1	85	22	25	0,889	1	1	16217 25 0
1	85	22	30	0,935	1	1	16217 30 0
1	85	22	35	0,970	1	1	16217 35 0

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM				
								Type	Dim.	Hand	Fin.	Pers. Spec.




- Deadbolt and latch
- 10.5 to 16.5 mm. adjustable latch and piston
- Set of nylon roses item 1.06012.01.0
- Pre-arranged for additional locking points
- Threaded pivots for fixing extended bolts
- 12 V ac SON REQUEST:
Internal ragged extended bolts item 1.06441.00.0
Internal straight extended bolts item 1.06441.10.0
Internal extended bolts item 1.06441.20.0
Pair of external bolt connectors item 1.06442.00.0
Extended bolts operated by internal rods item 1.06443.00.0
Extended bolts operated by external rods item 1.06443.05.0

1	85	22	25	0,845	1	1	16225 25 0
1	85	22	30	0,890	1	1	16225 30 0
1	85	22	35	0,935	1	1	16225 35 0




- Cross-key cylinder with 3 keys
- Dead-bolt and latch
- 10.5 to 16.5 mm. adjustable latch and piston
- Pre-arranged for additional locking points
- Set of nylon roses item 1.06002.00.0
- Threaded pivots for fixing extended bolts
- ON REQUEST:
Internal ragged extended bolts item 1.06441.00.0
Internal straight extended bolts item 1.06441.10.0
Internal extended bolts item 1.06441.20.0
External bolt connectors item 1.06442.00.0
Extended bolts operated by internal rods item 1.06443.00.0
Extended bolts operated by external rods item 1.06443.05.0

1	85	22	25	0,935	1	1	16227 25 0
1	85	22	30	0,996	1	1	16227 30 0
1	85	22	35	1,041	1	1	16227 35 0



- Dead-bolt only
- Set of nylon roses item 1.06012.01.0
- AS ABOVE
- U-shaped faceplate 24x5 mm
- Pair of spacers 3 and 5 mm


1	22	25	0,545	12	1	46210 25 0
1	22	30	0,575	12	1	46210 30 0
1	22	35	0,560	12	1	46210 35 0
1	24	25	0,550	12	1	46213 25 0
1	24	30	0,570	12	1	46213 30 0
1	24	35	0,590	12	1	46213 35 0



- Cross-key cylinder with 3 keys
- Dead-bolt only
- Set of nylon roses item 1.06002.00.0


1	22	25	0,650	12	1	46212 25 0
1	22	30	0,670	12	1	46212 30 0
1	22	35	0,690	12	1	46212 35 0

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM			
								Type	Dim.	Hand	Fin.




- Dead-bolt only
- Pre-arranged for additional locking points
- Set of nylon roses item 1.06012.01.0
- Threaded pivots for fixing extended bolts
- ON REQUEST:
Internal ragged extended bolts item 1.06441.00.0
Internal straight extended bolts item 1.06441.10.0
Internal extended bolts item 1.06441.20.0
External bolt connectors item 1.06442.00.0
Extended bolts operated by internal rods item 1.06443.00.0
Extended bolts operated by external rods item 1.06443.05.0

1	22	25	0,600	12	1	46220 25 0
1	22	30	0,620	12	1	46220 30 0
1	22	35	0,650	12	1	46220 35 0




- Cross-key cylinder with 3 keys
- Dead-bolt only
- Pre-arranged for additional locking points
- Set of nylon roses item 1.06002.00.0
- Threaded pivots for fixing extended bolts
- ON REQUEST:
Internal ragged extended bolts item 1.06441.00.0
Internal straight extended bolts item 1.06441.10.0
Internal extended bolts item 1.06441.20.0
External bolt connectors item 1.06442.00.0
Extended bolts operated by internal rods item 1.06443.00.0
Extended bolts operated by external rods item 1.06443.05.0

1	22	25	0,695	12	1	46222 25 0
1	22	30	0,690	12	1	46222 30 0
1	22	35	0,710	12	1	46222 35 0



- Dead-bolt and latch
- 11 to 17 mm. adjustable latch
- Set of nylon roses item 1.06012.01.0
- ON REQUEST: (SERIES 46215):
Stainless steel faceplate 25x3 mm with aligned fixing holes (pers. VV)
- AS ABOVE
- U-shaped faceplate 24x5 mm
- Pair of spacers 3 and 5 mm


1	85	22	25	0,610	12	1	46215 25 0
1	85	22	30	0,630	12	1	46215 30 0
1	85	22	35	0,660	12	1	46215 35 0
1	92	22	25	0,610	12	1	46219 25 0
1	92	22	30	0,616	12	1	46219 30 0
1	92	22	35	0,670	12	1	46219 35 0
1	92	24	25	0,620	12	1	46218 25 0
1	92	24	30	0,650	12	1	46218 30 0
1	92	24	35	0,660	12	1	46218 35 0



- Cross-key cylinder with 3 keys
- Dead-bolt and latch
- 11 to 17 mm. adjustable latch
- Set of nylon roses item 1.06002.00.0


1	85	22	25	0,730	12	1	46217 25 0
1	85	22	30	0,740	12	1	46217 30 0
1	85	22	35	0,770	12	1	46217 35 0

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM				
								Type	Dim.	Hand	Fin.	Pers. Spec.




- Dead-bolt and latch
- 11 to 17 mm. adjustable latch bolt
- Pre-arranged for additional locking points
- Set of nylon roses item 1.06012.01.0
- Threaded pivots for fixing extended bolts
- ON REQUEST:
Internal cranked extended bolts item 1.06441.00.0
Internal straight extended bolts item 1.06441.10.0
Internal extended bolts item 1.06441.20.0
External bolt connectors item 1.06442.00.0
Extended bolts operated by internal rods item 1.06443.00.0
Extended bolts operated by external rods item 1.06443.05.0
- Stainless steel faceplate 25x3 mm with aligned fixing holes (pers. VV)

1	85	22	25	0,650	12	1 46225 25 0
1	85	22	30	0,695	12	1 46225 30 0
1	85	22	35	0,700	12	1 46225 35 0




- Cross-key cylinder with 3 keys
- Dead-bolt and latch
- 11 to 17 mm. adjustable latch
- Pre-arranged for additional locking points
- Set of nylon roses item 1.06002.00.0
- Threaded pivots for fixing extended bolts
- ON REQUEST:
Internal ragged extended bolts item 1.06441.00.0
Internal straight extended bolts item 1.06441.10.0
Internal extended bolts item 1.06441.20.0
External bolt connectors item 1.06442.00.0
Extended bolts operated by internal rods item 1.06443.00.0
Extended bolts operated by external rods item 1.06443.05.0

1	85	22	25	0,750	12	1 46227 25 0
1	85	22	30	0,790	12	1 46227 30 0
1	85	22	35	0,790	12	1 46227 35 0



- Dead-bolt and roller
- 2.5 to 16.5 mm. adjustable roller
- Set of nylon roses item 1.06012.01.0
- ON REQUEST:
Stainless steel faceplate 25x3 mm with aligned fixing holes (pers. VV)
- AS ABOVE
- U-shaped faceplate 24x5 mm
- Pair of spacers 3 and 5 mm


1	22	25	0,600	12	1 46230 25 0
1	22	30	0,610	12	1 46230 30 0
1	22	35	0,635	12	1 46230 35 0
1	24	25	0,620	12	1 46233 25 0
1	24	30	0,640	12	1 46233 30 0
1	24	35	0,650	12	1 46233 35 0



- Dead-bolt and roller
- 2.5 to 16.5 mm. adjustable roller
- Pre-arranged for additional locking points
- Set of nylon roses item 1.06012.01.0
- Threaded pivots for fixing extended bolts
- ON REQUEST:
Internal ragged extended bolts item 1.06441.00.0
Internal straight extended bolts item 1.06441.10.0
Internal extended bolts item 1.06441.20.0
External bolt connectors item 1.06442.00.0
Extended bolts operated by internal rods item 1.06443.00.0
Extended bolts operated by external rods item 1.06443.05.0


1	22	25	0,630	12	1 46250 25 0
1	22	30	0,660	12	1 46250 30 0
1	22	35	0,685	12	1 46250 35 0

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM				
								Type	Dim.	Hand	Fin.	Pers. Spec.




- Cross-key cylinder with 3 keys
- Dead-bolt and latch
- 2.5 to 16.5 mm. adjustable roller
- Pre-arranged for additional locking points
- Set of nylon roses item 1.06002.00.0
- Threaded pivots for fixing extended bolts
- ON REQUEST:
Internal ragged extended bolts item 1.06441.00.0
Internal straight extended bolts item 1.06441.10.0
External bolt connectors item 1.06442.00.0
Extended bolts operated by internal rods item 1.06443.00.0
Extended bolts operated by external rods item 1.06443.05.0
Stainless steel faceplate 25x3 mm with aligned fixing holes (pers. VV)

1	22	25	0,730	12	1	46252	25	0			
1	22	30	0,760	12	1	46252	30	0			
1	22	35	0,790	12	1	46252	35	0			



- Laminar steel hook
- Set of nylon roses item 1.06012.01.0
- Zinc plated steel striking plate item 1.06459.01.0

1	22	25	0,580	12	1	46240	25	0			
1	22	30	0,610	12	1	46240	30	0			
1	22	35	0,630	12	1	46240	35	0			



- Laminar steel hook
- Pre-arranged for additional locking points
- Set of nylon roses item 1.06012.01.0
- Threaded pivots for fixing extended bolts
- Zinc plated steel striker item 1.06459.01.0
- ON REQUEST:
Internal ragged extended bolts item 1.06441.00.0
Internal straight extended bolts item 1.06441.10.0
External bolt connectors item 1.06442.00.0

1	22	25	0,625	12	1	46260	25	0			
1	22	30	0,650	12	1	46260	30	0			
1	22	35	0,710	12	1	46260	35	0			



- No frontal closure
- Pre-arranged for additional locking points
- Set of nylon roses item 1.06012.01.0
- Threaded pivots for fixing extended bolts
- ON REQUEST:
Internal ragged extended bolts item 1.06441.00.0
Internal straight extended bolts item 1.06441.10.0
External bolt connectors item 1.06442.00.0

	22	25	0,550	12	1	46270	25	0			
	22	30	0,580	12	1	46270	30	0			
	22	35	0,605	12	1	46270	35	0			