



**Technical features:**

- Zinc-plated steel case and striker
- Dead-locking latch
- 12 V ac CE
- Current absorption 2,5 A
- External cylinder length: 55 mm.

**Supplied as standard:**









- Striker
- Instruction sheet
- Fixing screws
- 3 keys item 1.01070.10.1











**Certifications:**

- This electric lock series is certified according to the European standard EN 14846:08:- Security degree 3 (500 Kg lateral push resistance and 200 Kg front push resistance)

**Hand:**

- 1 = R.H. inwards
- 2 = L.H. inwards
- 3 = R.H. outwards
- 4 = L.H. outwards

Type	Description	Cylinder	Throws	Backset	Unit weight Kg	Pieces	ITEM			
							Type	Dim.	Hand	Fin. Pars. Spec.
 <ul style="list-style-type: none"> <li>• Protective back plate</li> <li>• Spacer</li> </ul>	 <p>1 02139 00 0</p>	50	2,090	1	1 11721 50 1					
		50	2,095	1	1 11721 50 2					
		60	2,091	1	1 11721 60 1					
		60	2,085	1	1 11721 60 2					
		70	2,090	1	1 11721 70 1					
		70	2,090	1	1 11721 70 2					
		80	2,090	1	1 11721 80 1					
		80	2,060	1	1 11721 80 2					
 <ul style="list-style-type: none"> <li>• Protective back plate</li> <li>• Spacer</li> <li>• Push-button</li> <li>• Hold-open device</li> </ul>	 <p>1 02110 00 0</p>	50	2,100	1	1 11731 50 1					
		50	2,103	1	1 11731 50 2					
		60	2,085	1	1 11731 60 1					
		60	2,100	1	1 11731 60 2					
		70	2,100	1	1 11731 70 1					
		70	2,100	1	1 11731 70 2					
		80	2,100	1	1 11731 80 1					
		80	2,085	1	1 11731 80 2					
 <ul style="list-style-type: none"> <li>• Manual throw dead-bolt</li> <li>• Protective back plate</li> <li>• Spacer</li> </ul>	 <p>1 02145 00 1</p>	2 50	2,200	1	1 11761 50 1					
		2 50	2,218	1	1 11761 50 2					
		2 60	2,216	1	1 11761 60 1					
		2 60	2,210	1	1 11761 60 2					
		2 70	2,200	1	1 11761 70 1					
		2 70	2,222	1	1 11761 70 2					
		2 80	2,230	1	1 11761 80 1					
		2 80	2,250	1	1 11761 80 2					
 <ul style="list-style-type: none"> <li>• Manual throw dead-bolt</li> <li>• Protective back plate</li> <li>• Spacer</li> <li>• Push-button</li> </ul>	 <p>1 02145 00 0</p>	2 50	2,205	1	1 11771 50 1					
		2 50	2,205	1	1 11771 50 2					
		2 60	2,200	1	1 11771 60 1					
		2 60	2,220	1	1 11771 60 2					
		2 70	2,210	1	1 11771 70 1					
		2 70	2,210	1	1 11771 70 2					
		2 80	2,231	1	1 11771 80 1					
		2 80	2,251	1	1 11771 80 2					

Type	Description	Cylinder	Throws	Backset	Unit weight Kg	Pieces	ITEM					
							Type	Dim.	Hand	Fin.	Pers.	Spec.
	<ul style="list-style-type: none"> <li>• For automated and up-and-over gates</li> <li>• Protective back plate</li> <li>• External cylinder length: 70 mm.</li> </ul>	 1 02142 00 0	80	2,100	1	1	11823	80	1			
			80	2,100	1	1	11823	80	2			
		 1 02139 00 0	50	1,450	1	1	11921	50	1			
			50	1,450	1	1	11921	50	2			
			60	1,479	1	1	11921	60	1			
			60	1,472	1	1	11921	60	2			
			70	1,472	1	1	11921	70	1			
			70	1,476	1	1	11921	70	2			
			80	1,470	1	1	11921	80	1			
			80	1,475	1	1	11921	80	2			
	<ul style="list-style-type: none"> <li>• Push-button</li> <li>• Hold-open device</li> </ul>	 1 02110 00 0	50	1,475	1	1	11931	50	1			
			50	1,475	1	1	11931	50	2			
			60	1,470	1	1	11931	60	1			
			60	1,472	1	1	11931	60	2			
			70	1,475	1	1	11931	70	1			
			70	1,478	1	1	11931	70	2			
			80	1,470	1	1	11931	80	1			
			80	1,472	1	1	11931	80	2			
	<ul style="list-style-type: none"> <li>• FOR OUTWARD OPENING GATES</li> </ul>	 1 02139 00 0	50	1,539	1	1	11921	50	3			
			50	1,538	1	1	11921	50	4			
			60	1,534	1	1	11921	60	3			
			60	1,534	1	1	11921	60	4			
			70	1,533	1	1	11921	70	3			
			70	1,538	1	1	11921	70	4			
			80	1,539	1	1	11921	80	3			
			80	1,534	1	1	11921	80	4			
	<ul style="list-style-type: none"> <li>• FOR OUTWARD OPENING GATES</li> <li>• Push-button</li> <li>• Hold-open device</li> </ul>	 1 02110 00 0	50	1,536	1	1	11931	50	3			
			50	1,530	1	1	11931	50	4			
			60	1,532	1	1	11931	60	3			
			60	1,532	1	1	11931	60	4			
			70	1,530	1	1	11931	70	3			
			70	1,534	1	1	11931	70	4			
			80	1,532	1	1	11931	80	3			
			80	1,532	1	1	11931	80	4			